

32" BNC FRAMELESS LED MONITOR

24/7/365 Operating Capability



The 32" BNC frameless LED monitor is designed to excel in 24/7 video surveillance applications. Delivering full HD resolution and 16.7 million colours, the monitor displays every detail with precision. HDMI and VGA inputs and a BNC input/output easily accommodate multiple devices and allow for BNC looping. The monitor also features source auto detection and quick touch scalability for quick setup.

FEATURES

- 31.5" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- 178° Ultra-Wide Viewing Angle
- Source Auto Detection
- Low Blue Light Technology
- Quick Touch Scalability 16:9/4:3
- BNC, VGA, HDMI and Audio Inputs
- Includes VGA, Audio and Dual Power Cables (EU,UK)
- Two Built-In Speakers
- 36-Month Warranty
- Part #: CAP-32LED3-L
- UPC: 840049313491
- Length: 28.1" (715.2mm)
- Width: 7.7" (196.9mm)
- Height: 20.4" (518.3mm)
- Weight: 14.3 lbs. (6.5kg)
- UL Listed



MONITEUR BNC À DEL SANS CADRE DE 32 PO

Capacité de fonctionnement 24/7/365



Le moniteur BNC à DEL sans cadre de 32 po est parfait pour les applications de vidéosurveillance en permanence. Grâce à une résolution HD intégrale et à ses 16,7 millions de couleurs, ce moniteur saura afficher tous les détails avec précision. Les entrées HDMI et VGA et une entrée/sortie BNC accueillir plusieurs appareils et permettre le bouclage BNC. Le moniteur est aussi doté de fonctionnalités de détection automatique de la source et de mise à l'échelle pour une configuration facile.

CARACTÉRISTIQUES

- Dimensions d'achage diagonales de 31.5 po
- Résolution HD intégrale de 1920 x 1080P
- Grand angle de vue de 178°
- Détection automatique de la source
- Technologie à faible lumière bleue
- Modification rapide d'échelle 16:9/4:3
- Entrées BNC, VGA, HDMI et audio
- Comprend des câbles audio, VGA et Câble d'alimentation (EU, UK)
- Deux haut-parleurs intégrés
- Garantie de 36 mois
- N° de pièce: CAP-32LED3-L
- UPC: 840049313491
- Longueur: 28,1 po (715,2mm)
- Largeur: 7,7 po (196,9mm)
- Hauteur: 20,4 po (518,3mm)
- Poids: 14,3 lb (6,5kg)
- Homologué UL



TECHNICAL SPECIFICATIONS	
Model	CAP-32LED3-L
Screen Diagonal Dimension (inches)	31.5"
Viewable Area W x H	27.5" x 15.4" (698.5mm x 391.16mm)
LED Type	LED
Pixel Pitch (mm)	0.36375 x 0.36375mm
Screen Maximum Resolution	1920x1080
Display Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Supported Input Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Refresh Rate (hertz)	60Hz
Colour Depth (millions)	16.7 million colors
Brightness	300 nits (300cd/m ²)
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD selectable 16:9 or 4:3
Horizontal TV Lines	1080
Contrast Ratio	1200:1SCR
Response Time (ms)	8 ms (GTG)
View Angle H/V (degrees)	178° x 178°/CR>10
Digital Video Inputs	HDMI up to 1920x1080
Analog Video In/Out	VGA up to 1920x1080
Connectors	HDMI x 1 , VGA x 1 , BNC IN x 1 , BNC OUT x 1 , AUDIO OUT x 1
Audio Inputs (stereo)	1 x 3.5mm mini-jack
Speakers (watts)	2 x 3 watts
Stand-by (watts)	<0.5 watt
Power Consumption (watts)	34 watts typical
Monitor Body Dimensions	28.1" x 2.5" x 16.5" (715.2mm x 64mm x 421.2mm)
Dimensions Monitor+Stand	28.1" x 7.7" x 20.4" (715.2mm x 196.9mm x 518.3mm)
Panel Surface	Matte black
Case and Stand Material	Plastic
VESA Mounting Pattern (mm)	75mm x 75mm
Base/Stand Included	Yes
Base Tilt Angle	-5°-15°
Weight Cabinet Only	12.4 lbs. (5.65kg)
Weight Cabinet+Base Stand	14.3 lbs. (6.5kg)
Power Supply (internal)	AC 100-240V-50/60Hz 1.1A
Operating Temperature	0°C-40°C / 32°F-104°F
Storage Temperature	-20°C-50°C / -4°F-122°F
Operating Humidity	10-90%
Accessories Included in the Box	Dual power cable(EU,UK)/VGA cable/Audio cable/IR Remote/Stand support VESA Cover/Screws/Base of stand/User manuals
Mounting Screw Size (mm)	Screw for Mounting Monitor, Screws Type: M4-L14 mm/2pcs, M4-L18 mm/2pcs Screw for Base Of Stand Monitor, Screws Type: M6-L16 mm/1pcs
Certifications	CE/FCC/RoHS/HDMI/UL/WEEE/REACH/UKCA
Warranty	36 Months