SPEC SHEET



FULL HD PRO-GRADE LED COLOUR MONITOR

WBXML24



This professional grade widescreen LED 23.6" colour monitor offers HDMI, VGA, & BNC inputs. With an additional BNC looping output its versatility will allow it to work for any application. Boasting 16.7 million colours & FHD Resolution this monitor will make your video come to life.

- 23.6" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- VGA, BNC & HDMI Inputs
- 24/7 Operation
- IPS Technology, 178° Viewing Angle
- Source Auto Detection
- Quick Touch Scalability 16:9/4:3
- Includes Audio, VGA & Dual Power Cables (EU,UK)
- 36 Months Warranty

PART #: WBXML24

UPC: 811914029854

LENGTH:

21.88inch/555.9mm WIDTH:

5.87inch/149mm HEIGHT:

15.69inch/398.5mm

WEIGHT: 11.9lbs/5.4kg



SPEC SHEET



Model	WBXML24
Screen Diagonal Dimension (inches)	23.6
Viewable Area WxH (inches/mm)	20.52inch*11.54inch / 521mm*293mm
Led Type	LED
Pixel Pitch (mm)	0.2715x0.2715
Screen Maximum Resolution	1920x1080
Display Resolutions	640x480;800x600;1024x768;1280x1024;1366x768;1920x1080
Supported Input Resolutions	640x480;800x600;1024x768;1280x1024;1366x768;1920x1080
Refresh Rate (Hz)	60
Color Depth (M)	16.7
Brightness (cd/ m²)	250
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD selectable 16:9 or 4:3
Horizontal TV Lines	1080
Contrast Ratio	1000 :1SCR
Response Time (ms)	5(GTG)
View Angle H/V (degrees)	178°x 178°/CR>10
Digital Video Inputs	HDMI up to 1920 x1080
Analog Video In/Out	VGA up to 1920x1080, BNC CVBS looping
Audio Inputs (stereo)	1x3.5mm mini-jack
Speakers(W)	2 x 3
Stand-by(W)	< 0.5
Power Consumption	25W Typical
Monitor Body Dimensions (inches/mm)	21.88inchx13.28inchx2inch / 555.9mmx337mmx50.8mm
Dimensions Monitor+Stand (inches/mm)	21.88inchx15.69inchx5.87inch / 555.9mmx398.5mmx149mm
Panel Surface	Matte black
Case & Stand Material	Plastic
VESA Mounting Pattern (mm)	100 x 100
Base/Stand Included	Yes
Base Tilt Angle	-5°~15°
Weight Cabinet Only (lb/kg)	8.5lbs / 3.85kg
Weight Cabinet+Base Stand (lb/kg)	9.0lbs / 4.08kg
Power Supply (internal)	AC 100-240V~50/60Hz 1.1A
Operating Temperature	0°C~40°C / 32°F~104°F
Storage Temperature	-20°C~50°C / -4°F~122°F
Operating Humidity	10~90%
Accessories	Dual Power cable (EU,UK)/VGA cable/Audio cable/IR Remote/Batteries
	Hinge cover/Screws/Base of stand/Stand support/User manuals
Rack Mount Screw Size(mm)	Screws for Mounting Monitor, Screws Type: PMΦ4.0x6mm/4pcs/ PMΦ4.0x8mm/4pcs
	Screws for Securing Base of Stand, Screws Type: BBΦ4.0×7mm/5pcs
	Screws for Installing Monitor Stand, Screws Type: BMΦ4.0x8mm/2pcs
Certifications	CE/FCC/ROHS/HDMI/UL/WEEE/REACH
Warranty	36 Months