

FULL HD PRO-GRADE LED COLOUR MONITOR

24/7/365 Operating Capability

MODELS

WBXML32 31,5" (31.5" diagonal)

PANEL SPECIFICATIONS



FHD

Size	31.5" diagonal
Panel	FHD
Display scale	16:9
Backlight	ELED
Maximum resolution	1920x1080
Best working resolution	1920x1080@60Hz
Pixel Pitch	0.36mmx0.36mm
Active Area	698.5mmx392.9mm
Viewing angle	H:178°,V:178° (CR>10)
Center Luminance of White	Typ.:300cd/m ²
Contrast ratio	Typ.:3000:1
Response time	Typ.:5ms (GTG)
Display Colour	16.7 Million
Colour Gamut	Typ.:72% NTSC

INTERFACE CONFIGURATION (ALL MODELS)

Input Interface	HDMI	1
	VGA	1
	Audio In	1
	BNC (CVBS) In	1
	BNC (CVBS) Out	1

POWER MGT (ALL MODELS)

Size	31.5"
Power input	100V-240VAC 60/50Hz 1.1A
Working consumption	≤50W
Standby consumption	≤0.5W (auto wake up off model)
Audio power	5W×2

STRUCTURE SIZE

Model (all)	Metal construction
Size w×h×t (without base)	29" x 17.4" x 2.1" (736.6×441.9×49mm)
Size w×h×t (with base)	29" x 20.3" x 6.3" (736.6×515.6×160mm)
Size w×h×t Packing size (with base)	31.4" x 4.2" x 19.7" (800×109×502mm)
Weight (with base)	net weight 21.1 lbs (9.5 Kg) gross weight: 22.9 lbs (10.3 Kg)
Vesa	200mm×200mm

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.



www.wboxtech.com

MODELS

WBXML32 31,5" (31.5" diagonal)

FUNCTION PARAMETER (ALL MODELS)

System	Menu Language	English/French/Spanish/Italian Netherlands/Polish/Czech/Danish
	Sleep time setting	Yes
	Video format support	MJPEG,MPEG-1,MPEG-2, MPEG-4,H.264,FLV
	Audio format support	WAV
	Picture format support	JPG/JPEG,BMP,PNG
	Text format support	TEXT
Picture	Picture mode	User/Dynamic/Standard
	Colour temperature	User/Cool/Medium/Warm
	Comb filtering	3D
Sound	Sound mode	Standard/Music/Movie/Sports/User
	Mute	Yes
	Stereo Sound	Yes

ACCESSORY (ALL MODELS)

Stands Supports	2PCS
Base of Stands	2PCS
Remote control	1PCS
Batteries	2PCS
Allen Wrench	1PCS
User's Manual	2PCS
Hardware Pack (screws)	1PCS
Power cord	2PCS (EU & UK)
VGA Cable	1PCS
Audio Cable	1PCS

BEZEL SIZE/MM

Model	Left	Right	Top	Bottom
WBXML32	18.4	18.4	20	26.3

SAFETY & CERTIFICATION (ALL MODELS)


Safety (class I)	Withstand voltage strength	2.5KV DC/60s
	Leakage current	≤3.5mA(264V AC/60s)
	Earthing protective resistance	≤100mΩ(25A DC/20s)
Authentication	CE/FCC/ROHS/HDMI/UL/WEEE/REACH	
Remote control area	≥8m straight line ≥7m horizontal±30° and vertical±15°	
Environment	Working condition	Temperature: 0°C~40°C Humidity: 10%~90% Atmosphere: 86KPa~104KPa
	Storage condition	Temperature: -20°C~50°C Humidity: 5%~95% Atmosphere: 86KPa~104KPa



MODELS

WBXML32 31,5" (31.5" diagonal)

MOUNTING ON THE WALL



VESA MOUNTING

Model	Mounting Dimension	TOP	BOTTOM
WBXML32	200x200mm	HM6.0x10mm	HM6.0x10mm

*** HARDWARE INCLUDED IN MONITOR BOX**

Connecting

