

## ULTRA HD PRO-GRADE LED COLOUR MONITOR


24/7/365 Operating Capability

### MODELS

WBXML4K28 28" (28" diagonal)

### PANEL SPECIFICATIONS

**4K**  
ULTRA HD



Size	28" diagonal
Panel	UHD
Display scale	16:9
Backlight	ELED
Maximum resolution	3840x2160
Best working resolution	3840x2160@60Hz
Pixel Pitch	0.16mmx0.16mm
Active Area	649mmx369.3mm
Viewing angle	H:170°,V:160° (CR>10)
Center Luminance of White	Typ.:300cd/m <sup>2</sup>
Contrast ratio	Typ.:1000:1
Response time	Typ.:5ms (GTG)
Display Colour	1.073G
Colour Gamut	Typ.:72% NTSC

### POWER MGT (ALL MODELS)

Size	28"
Power input	100V-240VAC 60/50Hz 1.1A
Working consumption	≤45W
Standby consumption	≤0.5W (auto wake up off model)
Audio power	5Wx2

### STRUCTURE SIZE

Model (all)	Metal construction
Size wxhxt (without base)	26.04" x 15.31" x 2.07" (661.5x388.9x52.7mm)
Size wxhxt (with base)	26.04" x 18.22" x 6.29" (661.5x462.8x159.8mm)
Size wxhxt Packing size (with base)	28.3" x 4.2" x 17.5" (720x109x445mm)
Weight (with base)	net weight 17.1 lbs (7.8 Kg) gross weight: 19.1 lbs (8.7 Kg)
Vesa	100mmx100mm

### INTERFACE CONFIGURATION (ALL MODELS)

Input Interface	HDMI	1
	DVI	1
	VGA	1
	BNC (CVBS) In	2
	BNC (CVBS) Out	1
	Audio In	1
	Audio Out	1

USB	1
RS232 (RJ45) In	1
RS232 (RJ45) Out	1



FOR MORE INFORMATION,  
CONTACT YOUR ADI SALES PERSON.

[www.wboxtech.com](http://www.wboxtech.com)

## MODELS

WBXML4K28 28" (28" diagonal)

## FUNCTION PARAMETER (ALL MODELS)

System	Menu Language	English/French/Spanish/Italian Netherlands/Polish/Czech/Danish
	Sleep time setting	Yes
	Video format support	MJPEG,MPEG-1,MPEG-2, MPEG-4,H.264,FLV
	Audio format support	WAV
	Picture format support	JPG/JPEG,BMP,PNG
	Text format support	TEXT
	Picture	Picture mode
Colour temperature		User/Cool/Medium/Warm
Comb filtering		3D
Sound	Sound mode	Standard/Music/Movie/Sports/User
	Mute	Yes
	Stereo Sound	Yes

## ACCESSORY (ALL MODELS)

Stands Supports	2PCS
Base of Stands	2PCS
Remote control	1PCS
Batteries	2PCS
Allen Wrench	1PCS
User's Manual	2PCS
Hardware Pack (screws)	1PCS
Power cord	2PCS (EU & UK)
VGA Cable	1PCS
Audio Cable	1PCS

## BEZEL SIZE/MM

Model	Left	Right	Top	Bottom
WBXML4K28	19.3	19.3	18.8	20.6

## SAFETY & CERTIFICATION (ALL MODELS)


Safety (class I)	Withstand voltage strength	2.5KV DC/60s
	Leakage current	≤3.5mA(264V AC/60s)
	Earthing protective resistance	≤100mΩ(25A DC/20s)
Authentication	CE/FCC/ROHS/HDMI/UL/WEEE/REACH	
Remote control area	≥8m straight line ≥7m horizontal±30° and vertical±15°	
Environment	Working condition	Temperature: 0°C~40°C Humidity: 10%~90% Atmosphere: 86KPa~104KPa
	Storage condition	Temperature: -20°C~50°C Humidity: 5%~95% Atmosphere: 86KPa~104KPa



## MODELS

WBXML4K28 28" (28" diagonal)

## MOUNTING ON THE WALL



## VESA MOUNTING

Model	Mounting Dimension	TOP	BOTTOM
WBXML4K28	100x100mm	HM6.0x10mm	HM6.0x10mm

**\* HARDWARE INCLUDED IN MONITOR BOX**

## Connecting

