





THE SUN PROVIDES YOUR ENERGY, SANTON PROVIDES YOUR SAFETY

In most photovoltaic systems, the dc isolator is integrated into the dc/ac power inverter. After switching off the dc isolator, the cables between the dc solar modules and dc/ac power inverter running through the building are still subject to up to 1000 v dc. in the event of a fire, firefighters are exposed to a very serious source of potential danger. The santon firefighter safety switch (dfs) provides the solution. It directly disconnects the dc current in close proximity to the solar modules and creates a safer situation for firefighters.



1. GAIN VALUABLE TIME IN CASE OF A FIRE

The DFS works according to standard international firefighter routines, resulting in valuable time bein C power is shut down, the DFS will automatically switch off and isolate DC cables running between the PV modules and the inverter. Firefighters only have to follow their regular routine and do not have to waste valuable time eliminating the risk of DC power still present at these cables. In case the AC power is not shut down and the temperature reaches 100 C at the DFS unit it will automatically shut down the DC power as extra safety system.

2. COMPLETELY ISOLATE PV MODULES

The DFS is powered by a motorized X-type switch and can therefore be located directly at the PV modules. This minimizes the amount of cabling with dangerous high voltage and leads to a completely powerless situation in the house, maximizing safety when needed.

3. AUTO RESET

A power down situation can occur at any time and for many reasons. The DFS has an auto reset function. The DFS automatically switches off if the regular AC power is down for more than 5 sec and automatically switches on when the regular AC power is on again. No manual reset is necessary every time the power has been down! After check of the safety situation and when the AC main power is reconnected automatically the Santon Firefighter safety switch will switch on the DC power.

4. FOR USE IN INDUSTRIAL AND RESIDENTIAL PHOTOVOLTAIC INSTALLATIONS

By using this standard concept unit for either 1 or 2 strings it is possible to combine unlimited number of units to fix every size of installation. As option it is possible to connect all units to the same AC source in order to create a separate DC on- off operation by switching this specific AC source on — off that will operate all units at the same time. Again reset is done automatically AC on = DC on AC off = DC off.

These units can be easily retrofitted to existing or new installations


5. CONTAINS THE WORLD'S MOST POPULAR DC SWITCH

The DFS is equipped with the Santon X-type switch, which is the most popular DC switch for PV applications. The Santon 'snap-action' spring mechanism, with its response time of only 3 milliseconds, reduces the electric arc. In combination with the self-cleaning contacts, this increases durability and safety. Therefore the Santon X-type switch has been selected by many inverter manufacturers as their no. 1 DC switch.

6. CHOOSE THE WORLD'S LEADING DC SWITCHGEAR COMPANY

With over 80 years of experience in developing DC switchgear for many different companies in many different and heavy industries all over the world, Santon has proven itself to be a leading DC switchgear company. With the Santon Firefighter safety Switch, all knowledge and experience come together for you to keep your home, or industrial building with people and valuables safe. Choose the best firefighter switch available - the Santon Firefighter safety Switch.

AC POWER SHUT DOWN = DC POWER SHUT DOWN




1. MANUAL AC POWER SHUT DOWN

The first step for any firefighter in fighting a fire is to shut down the main AC power circuit. This makes it possible to start extinguishing the actual fire without the risk of electrocution. Santon developed the Firefighter safety Switch according to this standard international safety routine. This prevents firefighters from having to take any extra action in case of a fire, maximizing their and your safety in the event of a fire.

2. AUTOMATIC DC POWER SHUT DOWN

As soon as a firefighter shuts down the main AC circuit, the DFS will detect this. If this power down situation lasts longer than 5 seconds, the DFS will automatically switch to the OFF position. Since the DFS is located close to the PV modules, the high voltage DC current from the PV modules will be completely isolated, which leaves a safe situation for the firefighters when fighting a fire in the commercial or residential building.



Ratings accourding to IEC: EN 60947-3:2009/A1:2012/C1:2013/A2:2015 Cat PV-1 based on switching both the + and the - pole V DC 1000 800

A	16	20	25 32	
Typ DFS	Number of Strings	Number of Poles	Specs.	
DFS-14	2	4	Unit with knock outs	
DFS-14-W	2	4	Unit with cable glands 9 x M12	
DES-14-MC4	2	1	Unit pre-wired with 8 x MC4 connectors	

	ng to IEC: EN 60947 ng both the + and t	7-3:2009/A1:2012/C1:2013/A2:2015 Cat PV-1 he - pole:
V DC	1000	

Α	40			
Typ DFS	Number of Strings	Number of Poles	Specs.	

Unit pre-wired with 8 x MC4 connectors DFSHP-14-MC4 and 1 x M12 cable gland for AC

1. ROBUST ENCLOSURE

IP65 watertight / UV resistant / Designed for optimal switch access and ease of installation

2. SAFETY SEAL

Possible placement of safety seal for controlled maintenance

3. MOTOR-DRIVEN X-TYPE SWITCH

Santon's reliable X-type switch / Switch disconnection within 3m.sec / minimum arc / maximum lifetime

4. MECHANICAL POSITION INDICATION

Visual feedback of the switch position (GREEN/OFF and RED/ON)

5. TEMPERATURE SENSOR

The DFS will automatically switch to the off position in case the temperature rises above 100°C

6. POWER SUPPLY (UPS)

Power supply unit for remotely operating the switch

7. POWER CONNECTION

AC power connection for charging the power backup and for optional integration with a fire alarm system

8. PRESSURE EQUALISING VALVE


Avoids condensation inside the enclosure and ensures maximum endurance and lifetime


9. KNOCK OUTS

The DFS is supplied with 10 x 12mm knockouts

10. CABLE GLANDS OR MC4 CONNECTORS

The DFS can be ordered pre-wired with MC4 connectors or with seperately delivered cable glands M12





WWW.SANTONSWITCHGEAR.COM

Santon Holland by

DFS-14-MC4

The Netherlands. Tel: +31(0)10 283 26 00 Fax: +31(0)10 429 45 46 info@santonswitchgear.com EN-ISO 9001:2015

Santon International

The Netherlands Tel: +31(0)10 283 26 00 Fax: +31(0)10 429 45 46 info@santonswitchgear.com EN-ISO 9001:2015

and 1 x M12 cable gland for AC

Santon Switchgear Ltd

United Kingdom Tel: +44(0)1633-252371 Fax: +44(0)1633-254277 info@santonswitchgear.co.uk EN-ISO 9001:2015

Santon GmbH

Germany Tel: +49(0)180 118 40 88 Fax: +49(0)180 118 41 99 info@santonswitchgear.com EN-ISO 9001:2015